

PATENT SPECIFICATION

687,041



Date of Application and filing Complete Specification March 6, 1951.

No. 5416/51.

Application made in United States of America on March 20, 1950.

Complete Specification Published Feb. 4, 1953

Index at acceptance:—Class 96, B(1: 6: 11b), B13(c: e: il), B16.

COMPLETE SPECIFICATION

Paper Making

We, AMERICAN VISCOSE CORPORATION, of Philadelphia, in the State of Pennsylvania, United States of America, a Corporation organized and existing under and by virtue of the laws of the State of Delaware, United States of America, do hereby declare the invention, for which we pray that a patent may be granted to us, and the method by which it is to be performed, to be particularly described in and by the following statement:—

The present invention relates to the art of making paper from artificial fibres, in whole or in part, such as those formed from regenerated cellulose.

The art of making paper depends upon the fibrillation which occurs when paper-making fibre is beaten in water. The fibrillation manifests itself by a fraying of the surfaces and ends of the fibres in a manner to produce minute tendrils or fibrillae which serve to felt or lock the fibres together when they are subjected to the paper-making process.

Recently, means have been found to cut regenerated cellulose fibres, such as those formed from viscose, to the prescribed paper-making length. However, regenerated cellulose fibres have not been considered as paper-making fibres due to their high swelling, softening, slipperiness, and inability to disperse in water and to fibrillate so as to hold the fibre web together sufficiently to permit its removal from the paper-making screen as a sheet. The presently employed practice of forming paper comprising regenerated cellulose fibres is to introduce the same into a previously beaten paper-making fibre of cotton, wood, manilla or other paper stock, at the beater, and without further beating other than mixing, cast them into the paper sheet with the fibrillating paper-making fibre acting as a dispersing, carrying, and bonding medium. Such sheets, however, when a substantial amount of regenerated cellulose fibres have been added have been characterized

by a high degree of porosity, softness and weakness which limit their use to restricted special applications.

Further, the use of the ordinary or conventional paper-making non-fibrous binders, bonding agents, or cements, such as glues, starches, or sodium silicate, which are applied in solution form and then dried, have not proved successful with regenerated cellulose fibres. This is probably due to the fact that conventional non-fibrous binders do not possess sufficient binding strength to cause the regenerated cellulose fibres to bind together to give the resultant sheet sufficient strength. In fact, conventional bonding agents are so lacking in binding strength for this purpose that a regenerated cellulose fibre web employing such binders is so weak structurally that the same cannot be removed while wet from the paper-making wire as a sheet.

According to the present invention, there is provided a paper sheet comprising fibrillated regenerated cellulose fibres.

The objects of the present invention are in general accomplished by beating in an ordinary paper beater, a special high strength low elongation viscose rayon fibre, which is described in detail herein-after, for a period which corresponds to normal paper beating time. During the beating operation the fibre remains constricted, i.e., does not swell to any appreciable extent, is reduced to paper-making length, and becomes readily dispersible. Above all the regenerated cellulose fibre fibrillates both at its ends and irregularly along its length. The beaten fibrillated fibre is then diluted to proper consistency and cast on the paper-making screen or wire and removed therefrom as a self-sustaining sheet without the addition of other fibres or bonding additives.

Ordinary regenerated cellulose or viscose rayon fibre does not fibrillate when subjected to beating in an ordinary paper beater. Consequently, the same has not

[Price 2/8] 3s 6d.

687,041

been useful as a papermaking fibre when used alone up until the present. It has now been discovered, however, that viscose rayon fibres produced as hereinafter described will fibrillate when subjected to the ordinary paper-beating operation.

Viscose which has been prepared in the usual manner is employed in making the fibrillating rayon fibre. The viscose is one which has a salt point of 3 to 6 (NaCl), cellulose content from 6 to 9%, and a NaOH content from 6 to 9%. During the process of manufacture, the alkali cellulose crumbs are aged for such a length of time so as to give a viscose having a ball fall viscosity between 65 and 120 seconds.

The viscose is passed through a spinneret into a coagulating bath to liberate the cellulose xanthate without substantial regeneration of the cellulose. The cellulose xanthate fibre thus formed is then subjected to considerable stretching which orientates the molecules in the fibre and increases the crystallinity, these two properties being determinative of the fibrillating property of the finished fibre. After stretching the fibre is passed into a regenerating bath, after which the regenerated cellulose fibre is sent directly to the usual finishing stages through which such fibres are usually passed in the normal course of their production.

Various chemical compounds may be employed in the coagulating and regenerating baths such as sulphuric acid, phosphoric acid, boric acid, acetic acid, sodium sulphate, sodium acetate, ammonium sulphate, mono- and di-basic sodium phosphate, etc.

For example, a satisfactory fibrillating viscose rayon fibre may be produced when a coagulating bath is employed having a pH in the range of 1.5 to 10 and comprising between 5 and 20% by weight of phosphate radicals and between 5 and 20% by weight of sodium sulphate, the temperature of such bath being main-

tained at room temperature or higher and preferably between 45 and 55° C. In conjunction with this coagulating bath a regenerating bath should be employed comprising 1 to 15% by weight of sulphuric acid. Because of the carry-over of coagulating solution in the regenerating bath by the fibre, the regenerating bath should be so regulated that it contains at all times 5 to 10% phosphoric acid and 10 to 20% sodium sulphate. The temperature of the regenerating bath is the same as that of the coagulating bath.

Fibres produced as outlined above, exhibit high tensile strengths (wet and dry), combined with low extensibilities (wet and dry) and low swellings (cross-sectional and linear) upon exposure to water or water vapour.

Average fibre properties are tabulated below:—

Tenacity (Dry)	- - 4.5 grams/denier
Tenacity (Wet)	- - 3.0 grams/denier
Extensibility (Dry)	- 8.0%
Extensibility (Wet)	- 8.0%
Cross-sectional Swelling	- - - 40%
Linear Swelling	- - - 0.25%

These fibres also possess the proper orientation and crystallinity that is necessary for fibrillation.

The fibre properties of other fibrillated artificial fibres will vary within the range of values tabulated below:—

Tenacity (Dry)	- - 3—5 grams/denier
Tenacity (Wet)	- - 2—3.5
Extensibility (Dry)	6—10%
Extensibility (Wet)	6—10%
Cross-sectional Swelling	- - - 35—45%
Linear Swelling	- 0.20—0.50%

In the following table there is tabulated the range of orientation and crystallinity values for the fibrillated viscose rayon fibre of the present invention as compared to those for a fibrillating natural cellulose fibre and a normal viscose rayon fibre which is non-fibrillating.

Fibre	TABLE I.	
	% Crystallinity	Orientation Half maximum angle in degrees
Hemp	92—96	12—17
Fibrillating Viscose Rayon Fibre	85—91	18—24
Regular Viscose Rayon Fibre	75—82	25—32

The percent crystallinity, as expressed in the table, is defined as the percent residue by weight after treatment in 2.5 normal hydrochloric acid for 15 minutes at 105—0.5° C. The orientation is expressed in terms of the half maximum angle as determined from X-ray diffrac-

tion. The half maximum angle is the angular length in degrees of the 002 interference (Miller Index) in the X-ray diagram of rayon at half the maximum intensity after a correction for background intensity. (See Ingersoll, H.G., J. Applied Physics 17, 924 (1946)).

From the values in the table, it can be seen that the orientation and crystallinity of the viscose rayon fibre of the present invention approaches that for hemp, which readily fibrillates even when the same is placed in water and stirred gently. It appears that both the proper orientation and crystallinity are necessary. That is to say that even though a fibre possesses the proper orientation, but not the proper crystallinity, or *vice versa*, it will not necessarily fibrillate. It further appears that the ideal fibre, insofar as fibrillation is concerned, would be one having 0° orientation and 100% crystallinity.

As previously pointed out, the viscose rayon fibres, produced as herein pointed out, are beaten in a standard paper beater for a period of 3 to 12 or more hours at concentrations of approximately 0.5 to 3.0%. However, when a laboratory beater is employed, a beating time of 1 to 2 hours is sufficient. The fibres fibrillate at their ends and irregularly along their lengths and disperse readily. The resultant fibrillated viscose rayon fibre dispersion may be diluted to any desired consistency, depending on the type sheet or web it is desired to produce, and cast on the paper-making screen or wire and removed therefrom as a self-sustaining sheet or web. The sheet may be formed on conventional paper-making machines of various types, such as the Fourdrinier, Harper, single cylinder or Yankee, multi-
 35 vat machine, mould, presse pate, or the like.

The fibrillated fibre-dispersion may be diluted to approximately 0.5 to 0.002%. For example, in making a tea bag paper, a concentration of approximately 0.002% is satisfactory, whereas in making filter paper, mimeograph paper, and the like, a concentration of approximately 0.02% would be sufficient.

While the invention has been described in connection with forming a sheet or web comprising 100% fibrillated viscose rayon fibres, various other fibrillating and non-fibrillating fibres may be incorporated therewith. Also various bonding agents may be added if desired. For example, varying amounts of a fibrillating fibre may be added to the fibrillated viscose rayon fibre in the beater, such as cotton, hemp, flax, and the like. Non-fibrillating fibres such as those formed from cellulose acetate, cellulose nitrate, casein, water-insoluble cellulose ethers, etc., may be employed. The bonding agents, such as glue, cellulose ethers, and the like, may be added to the fibrillated viscose rayon fibre or a mixture of the same with fibrillating or non-fibrillating material.

65 Further, the fibrillated viscose rayon

fibre of the present invention may be used to form sheets or webs of non-fibrillating fibres such as cellulose acetate, cellulose nitrate, ordinary rayon, etc. From 2 to 10% of the fibrillated viscose rayon fibre mixed with 90 to 98% of the non-fibrillated fibre would be sufficient to form a self-sustaining sheet on the screen or wire.

Various heat activatable, thermoplastic, or thermosetting (when in a thermoplastic state), resinous fibres may be employed with the fibrillating viscose rayon fibres. The fibrillae of the latter enable the formation of a self-sustaining sheet or web which later may be subjected to heat and pressure thus activating the thermosetting or thermoplastic resinous fibres which form a smooth, tough sheet having a high gloss making the same suitable for magazine papers and the like. Examples of thermoplastic resinous fibres are those formed from high molecular weight synthetic linear polyamides or polyesters, copolymers of vinyl chloride and vinylidene chloride, vinyl acetate, polyethylene, polyacrylonitrile, and the like. Examples of the thermosetting resinous fibres are those formed from urea-aldehydes, phenyl-aldehydes and the like.

Other shaped articles may be formed from the dispersion of fibrillated viscose rayon fibres of the instant invention. The dispersion may be applied to various shaped mandrels such as used in making hats, brassieres, and the like. This is particularly advantageous when thermosetting or thermoplastic resinous fibres are incorporated with the fibrillating viscose rayon fibres.

The fibrillating viscose rayon fibres may vary in denier from 0.75 to 5.5 and when beaten in the paper beater a fibre length between 1 mm. and 10 mm. is satisfactory. Here again the denier and fibre length will vary in accordance with the desired properties in the end product.

The sheets or webs and other shaped articles formed from the fibrillated viscose rayon fibres have many and varied uses. For example they are useful in the manufacture of tea bags, mimeograph and overlay paper, filtering paper, papers used for wiping such as facial or toilet tissues, magazine and book paper etc. Various materials may be incorporated in the fibrillated viscose rayon fibre sheets such as dyes, pigments, various plasticizers, waterproofing agents, greaseproof agents, mildew-preventative agents, fillers, and the like.

What we claim is:—

1. A paper sheet comprising fibrillated regenerated cellulose fibres.
2. A paper sheet according to claim 1,

100
 105
 110
 115
 120
 125
 130
 135
 140
 145
 150
 155
 160
 165
 170
 175
 180
 185
 190
 195
 200
 205
 210
 215
 220
 225
 230
 235
 240
 245
 250
 255
 260
 265
 270
 275
 280
 285
 290
 295
 300
 305
 310
 315
 320
 325
 330
 335
 340
 345
 350
 355
 360
 365
 370
 375
 380
 385
 390
 395
 400
 405
 410
 415
 420
 425
 430
 435
 440
 445
 450
 455
 460
 465
 470
 475
 480
 485
 490
 495
 500
 505
 510
 515
 520
 525
 530
 535
 540
 545
 550
 555
 560
 565
 570
 575
 580
 585
 590
 595
 600
 605
 610
 615
 620
 625
 630
 635
 640
 645
 650
 655
 660
 665
 670
 675
 680
 685
 690
 695
 700
 705
 710
 715
 720
 725
 730
 735
 740
 745
 750
 755
 760
 765
 770
 775
 780
 785
 790
 795
 800
 805
 810
 815
 820
 825
 830
 835
 840
 845
 850
 855
 860
 865
 870
 875
 880
 885
 890
 895
 900
 905
 910
 915
 920
 925
 930
 935
 940
 945
 950
 955
 960
 965
 970
 975
 980
 985
 990
 995
 1000
 1005
 1010
 1015
 1020
 1025
 1030
 1035
 1040
 1045
 1050
 1055
 1060
 1065
 1070
 1075
 1080
 1085
 1090
 1095
 1100
 1105
 1110
 1115
 1120
 1125
 1130
 1135
 1140
 1145
 1150
 1155
 1160
 1165
 1170
 1175
 1180
 1185
 1190
 1195
 1200
 1205
 1210
 1215
 1220
 1225
 1230
 1235
 1240
 1245
 1250
 1255
 1260
 1265
 1270
 1275
 1280
 1285
 1290
 1295
 1300
 1305
 1310
 1315
 1320
 1325
 1330
 1335
 1340
 1345
 1350
 1355
 1360
 1365
 1370
 1375
 1380
 1385
 1390
 1395
 1400
 1405
 1410
 1415
 1420
 1425
 1430
 1435
 1440
 1445
 1450
 1455
 1460
 1465
 1470
 1475
 1480
 1485
 1490
 1495
 1500
 1505
 1510
 1515
 1520
 1525
 1530
 1535
 1540
 1545
 1550
 1555
 1560
 1565
 1570
 1575
 1580
 1585
 1590
 1595
 1600
 1605
 1610
 1615
 1620
 1625
 1630
 1635
 1640
 1645
 1650
 1655
 1660
 1665
 1670
 1675
 1680
 1685
 1690
 1695
 1700
 1705
 1710
 1715
 1720
 1725
 1730
 1735
 1740
 1745
 1750
 1755
 1760
 1765
 1770
 1775
 1780
 1785
 1790
 1795
 1800
 1805
 1810
 1815
 1820
 1825
 1830
 1835
 1840
 1845
 1850
 1855
 1860
 1865
 1870
 1875
 1880
 1885
 1890
 1895
 1900
 1905
 1910
 1915
 1920
 1925
 1930
 1935
 1940
 1945
 1950
 1955
 1960
 1965
 1970
 1975
 1980
 1985
 1990
 1995
 2000
 2005
 2010
 2015
 2020
 2025
 2030
 2035
 2040
 2045
 2050
 2055
 2060
 2065
 2070
 2075
 2080
 2085
 2090
 2095
 2100
 2105
 2110
 2115
 2120
 2125
 2130
 2135
 2140
 2145
 2150
 2155
 2160
 2165
 2170
 2175
 2180
 2185
 2190
 2195
 2200
 2205
 2210
 2215
 2220
 2225
 2230
 2235
 2240
 2245
 2250
 2255
 2260
 2265
 2270
 2275
 2280
 2285
 2290
 2295
 2300
 2305
 2310
 2315
 2320
 2325
 2330
 2335
 2340
 2345
 2350
 2355
 2360
 2365
 2370
 2375
 2380
 2385
 2390
 2395
 2400
 2405
 2410
 2415
 2420
 2425
 2430
 2435
 2440
 2445
 2450
 2455
 2460
 2465
 2470
 2475
 2480
 2485
 2490
 2495
 2500
 2505
 2510
 2515
 2520
 2525
 2530
 2535
 2540
 2545
 2550
 2555
 2560
 2565
 2570
 2575
 2580
 2585
 2590
 2595
 2600
 2605
 2610
 2615
 2620
 2625
 2630
 2635
 2640
 2645
 2650
 2655
 2660
 2665
 2670
 2675
 2680
 2685
 2690
 2695
 2700
 2705
 2710
 2715
 2720
 2725
 2730
 2735
 2740
 2745
 2750
 2755
 2760
 2765
 2770
 2775
 2780
 2785
 2790
 2795
 2800
 2805
 2810
 2815
 2820
 2825
 2830
 2835
 2840
 2845
 2850
 2855
 2860
 2865
 2870
 2875
 2880
 2885
 2890
 2895
 2900
 2905
 2910
 2915
 2920
 2925
 2930
 2935
 2940
 2945
 2950
 2955
 2960
 2965
 2970
 2975
 2980
 2985
 2990
 2995
 3000
 3005
 3010
 3015
 3020
 3025
 3030
 3035
 3040
 3045
 3050
 3055
 3060
 3065
 3070
 3075
 3080
 3085
 3090
 3095
 3100
 3105
 3110
 3115
 3120
 3125
 3130
 3135
 3140
 3145
 3150
 3155
 3160
 3165
 3170
 3175
 3180
 3185
 3190
 3195
 3200
 3205
 3210
 3215
 3220
 3225
 3230
 3235
 3240
 3245
 3250
 3255
 3260
 3265
 3270
 3275
 3280
 3285
 3290
 3295
 3300
 3305
 3310
 3315
 3320
 3325
 3330
 3335
 3340
 3345
 3350
 3355
 3360
 3365
 3370
 3375
 3380
 3385
 3390
 3395
 3400
 3405
 3410
 3415
 3420
 3425
 3430
 3435
 3440
 3445
 3450
 3455
 3460
 3465
 3470
 3475
 3480
 3485
 3490
 3495
 3500
 3505
 3510
 3515
 3520
 3525
 3530
 3535
 3540
 3545
 3550
 3555
 3560
 3565
 3570
 3575
 3580
 3585
 3590
 3595
 3600
 3605
 3610
 3615
 3620
 3625
 3630
 3635
 3640
 3645
 3650
 3655
 3660
 3665
 3670
 3675
 3680
 3685
 3690
 3695
 3700
 3705
 3710
 3715
 3720
 3725
 3730
 3735
 3740
 3745
 3750
 3755
 3760
 3765
 3770
 3775
 3780
 3785
 3790
 3795
 3800
 3805
 3810
 3815
 3820
 3825
 3830
 3835
 3840
 3845
 3850
 3855
 3860
 3865
 3870
 3875
 3880
 3885
 3890
 3895
 3900
 3905
 3910
 3915
 3920
 3925
 3930
 3935
 3940
 3945
 3950
 3955
 3960
 3965
 3970
 3975
 3980
 3985
 3990
 3995
 4000
 4005
 4010
 4015
 4020
 4025
 4030
 4035
 4040
 4045
 4050
 4055
 4060
 4065
 4070
 4075
 4080
 4085
 4090
 4095
 4100
 4105
 4110
 4115
 4120
 4125
 4130
 4135
 4140
 4145
 4150
 4155
 4160
 4165
 4170
 4175
 4180
 4185
 4190
 4195
 4200
 4205
 4210
 4215
 4220
 4225
 4230
 4235
 4240
 4245
 4250
 4255
 4260
 4265
 4270
 4275
 4280
 4285
 4290
 4295
 4300
 4305
 4310
 4315
 4320
 4325
 4330
 4335
 4340
 4345
 4350
 4355
 4360
 4365
 4370
 4375
 4380
 4385
 4390
 4395
 4400
 4405
 4410
 4415
 4420
 4425
 4430
 4435
 4440
 4445
 4450
 4455
 4460
 4465
 4470
 4475
 4480
 4485
 4490
 4495
 4500
 4505
 4510
 4515
 4520
 4525
 4530
 4535
 4540
 4545
 4550
 4555
 4560
 4565
 4570
 4575
 4580
 4585
 4590
 4595
 4600
 4605
 4610
 4615
 4620
 4625
 4630
 4635
 4640
 4645
 4650
 4655
 4660
 4665
 4670
 4675
 4680
 4685
 4690
 4695
 4700
 4705
 4710
 4715
 4720
 4725
 4730
 4735
 4740
 4745
 4750
 4755
 4760
 4765
 4770
 4775
 4780
 4785
 4790
 4795
 4800
 4805
 4810
 4815
 4820
 4825
 4830
 4835
 4840
 4845
 4850
 4855
 4860
 4865
 4870
 4875
 4880
 4885
 4890
 4895
 4900
 4905
 4910
 4915
 4920
 4925
 4930
 4935
 4940
 4945
 4950
 4955
 4960
 4965
 4970
 4975
 4980
 4985
 4990
 4995
 5000
 5005
 5010
 5015
 5020
 5025
 5030
 5035
 5040
 5045
 5050
 5055
 5060
 5065
 5070
 5075
 5080
 5085
 5090
 5095
 5100
 5105
 5110
 5115
 5120
 5125
 5130
 5135
 5140
 5145
 5150
 5155
 5160
 5165
 5170
 5175
 5180
 5185
 5190
 5195
 5200
 5205
 5210
 5215
 5220
 5225
 5230
 5235
 5240
 5245
 5250
 5255
 5260
 5265
 5270
 5275
 5280
 5285
 5290
 5295
 5300
 5305
 5310
 5315
 5320
 5325
 5330
 5335
 5340
 5345
 5350
 5355
 5360
 5365
 5370
 5375
 5380
 5385
 5390
 5395
 5400
 5405
 5410
 5415
 5420
 5425
 5430
 5435
 5440
 5445
 5450
 5455
 5460
 5465
 5470
 5475
 5480
 5485
 5490
 5495
 5500
 5505
 5510
 5515
 5520
 5525
 5530
 5535
 5540
 5545
 5550
 5555
 5560
 5565
 5570
 5575
 5580
 5585
 5590
 5595
 5600
 5605
 5610
 5615
 5620
 5625
 5630
 5635
 5640
 5645
 5650
 5655
 5660
 5665
 5670
 5675
 5680
 5685
 5690
 5695
 5700
 5705
 5710
 5715
 5720
 5725
 5730
 5735
 5740
 5745
 5750
 5755
 5760
 5765
 5770
 5775
 5780
 5785
 5790
 5795
 5800
 5805
 5810
 5815
 5820
 5825
 5830
 5835
 5840
 5845
 5850
 5855
 5860
 5865
 5870
 5875
 5880
 5885
 5890
 5895
 5900
 5905
 5910
 5915
 5920
 5925
 5930
 5935
 5940
 5945
 5950
 5955
 5960
 5965
 5970
 5975
 5980
 5985
 5990
 5995
 6000
 6005
 6010
 6015
 6020
 6025
 6030
 6035
 6040
 6045
 6050
 6055
 6060
 6065
 6070
 6075
 6080
 6085
 6090
 6095
 6100
 6105
 6110
 6115
 6120
 6125
 6130

characterized in that said fibres are high strength, low elongation fibres.

3. A paper sheet according to claim 1 or 2, characterized in that said artificial fibres have an orientation of 18 to 24° and a crystallinity of 85 to 91%.

4. A paper sheet according to any of claims 1-3, characterized in that it com-

prises 90 to 98% of non-fibrillated fibres and 2 to 10% of said fibrillated artificial 10 fibres.

RAYNOR & CO.,

Bank Chambers,

29, Southampton Buildings,

Chancery Lane, London, W.C.2,

Agents for the Applicants.

Leamington Spa: Printed for Her Majesty's Stationery Office, by the Courier Press.—1953.

Published at The Patent Office, 25, Southampton Buildings, London, W.C.2, from which copies may be obtained.

- Fib rayon

- Primary

- Microfibers

- other microfibers or other fibers

2.5-6.5

3-20% fibrillated rayon } primary 490
 } Microfibers < 1mm at 50% 350
 840

Non-fibrillated rayon + pulp < 10mm

1350
 840
 510